

Thickness: 5.0 mm Total (4mm SPC + 1mm EVA)
Wear Layer: 20 MIL

Plank Size:	8.86" Wide x 60" Long (Wood Grain Texture)
Installation:	Click System - Floating
W arranty:	Lifetime Residential Wear Warranty, Lifetime Structural Warranty Limited Lifetime Waterproof Warranty, 10 Year Limited Light Commercial Warranty
Wear Resistance (EN13329):	>4000 cycles - Classification (Class 34)
Impact Resistance (EN13329):	>1800mm - Classification (Class 34)
Micro-Scratch Resistance:	ISO 15 18 - 1 - ≥ 3 2 0 0 g
Static Load (250>BS/115KG:	ASTM F970 - 15 - Class 4 Heavy Commercial
IIC/STC:	IIC: 68 STC: 61
Locking Strength:	Long Side ≥ 6.3kn/m Short Side ≥ 5.4 kn/m
Resistance to Staining:	No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium, hydroxide (NaOH), hydrogen peroxide (h2O2), shoe polish.
Fire Resistance:	ASTM E648/662 - 1.09 W/cm2 - Class 1
Fungi Resistance ASTM G21-15:	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore®	SCS-FS-04026 2020.06.01-2021.05.31
	Packaging:
Content of Box:	(8.86" x 60" - 22.12 Sq.Ft./ Box)

Content of Pallet: 56 cartons per Pallet