

Product Specifications / Technical Data



Collection Name: Premier XL

Effective: April 7, 2017

Composition:	Phthalate-Free Virgin Vinyl
Size (inches / mm):	8.75" x 59.75" (222.25 x 1517.65mm)
Gauge:	4.5mm
Wear Layer:	20mil (.5mm)
Finish:	G55 Advanced Coating System
Edge:	Bevel
Sq.Ft. / Piece:	3.63
Sq.Ft. / Carton:	21.78
Pieces / Carton:	6
Cartons / Pallet:	48 (1,045.44 sq.ft.)
Pallets / 20' Container:	20 (20,908 sq.ft.)
Weight / Carton:	41.52lbs
Weight / Pallet:	2,032.96lbs
Limited Warranty:	Lifetime Residential 10 Year Commercial

Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes