

Product Specifications / Technical Data



Collection Name:

Effective: Oct 1, 2017

Composition:	Recycled Vinyl – Fiberglass Sheet – L-Shaped Grout
Size (inches / mm):	Plank: 7.08" x 47.24" (179.83 x 1199.89mm) Plank: 36" x 36" (914.4 x 914.4mm) Tile: 18" x 36" (457.2 x 914.4mm)
Gauge:	1/6" (4.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Urethane Coating System
Edge:	Built in L-Shaped Grout
Sq.Ft. / Piece:	Plank: 2.32 - 7.08" Tile: 9 - 36" Tile: 4.5 - 18"
Sq.Ft. / Carton:	Plank: 27.9 - 7.08" Tile: 36 - 36" Tile: 36 - 18"
Pieces / Carton:	Plank: 12-7.08" Tile: 4 - 36" Tile: 8 - 18"
Cartons / Pallet:	Plank: 50 (1,395 sq.ft.)-7.08" Tile: 34 (1,224 sq.ft.)-36" Tile: 34 (1,224 sq.ft.)-18"
Limited Warranty:	Lifetime Residential 10 Year Commercial
Testing	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
Slip Resistance:	Meets and exceeds passing requirements for ADA and OSHA Guidelines (>.6)
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
Sustainability	
Recycled Content:	Yes
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements

Revised: 04/10/2018

www.casabellafloors.com