



Product Specifications / Technical Data

Collection Name: Freedom

Fttec	tive. I	IIne	"	2016

Composition:	Phthalate-Free Virgin Vinyl		
Size (inches / mm):	7.08" x 47.24" (179.83 x 1199.89mm)		
Gauge:	.098" (2.5mm)		
Wear Layer:	12mil (.3mm)		
Finish:	G88 Advanced Coating System		
Edge:	Square		
Sq.Ft. / Piece:	2.32		
Sq.Ft. / Carton:	34.88		
Pieces / Carton:	15		
Cartons / Pallet:	60 (2092.8 sq.ft.)		
Pallets / 53' Truck:	22 (46,041.60 sq.ft.)		
Weight / Carton:	29lbs		
Weight / Pallet:	1,786lbs		
	25 Year Residential		
Limited Warranty:	10 Year Commercial		
,	esting		
,	Class III, Type B, Embossed Surface		
,			
Te	Class III, Type B, Embossed Surface		
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel	Class III, Type B, Embossed Surface Meets and exceeds passing requirements		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Class III, Type B, Embossed Surface Meets and exceeds passing requirements		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1)		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance) ASTM F925 – Resistance to Chemicals: ASTM F970 - Static Load Limit:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements (1,000 PSI-Modified)		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance) ASTM F925 – Resistance to Chemicals: ASTM F970 - Static Load Limit:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance) ASTM F925 – Resistance to Chemicals: ASTM F970 - Static Load Limit:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements (1,000 PSI-Modified)		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance) ASTM F925 – Resistance to Chemicals: ASTM F970 - Static Load Limit:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements Meets and exceeds passing requirements Meets and exceeds passing requirements (1,000 PSI-Modified)		
ASTM F1700 – Product Classification: ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance) ASTM F925 – Resistance to Chemicals: ASTM F970 - Static Load Limit: Susta	Class III, Type B, Embossed Surface Meets and exceeds passing requirements Meets and exceeds passing requirements (Class 1) Meets and exceeds passing requirements (1,000 PSI-Modified) iinability No		

Casabella Floors www.casabellafloors.com Phone: (847) 979-2500 - Fax: (847) 364-9207