



# Renaissance Collection 2.0 & 3.0

## Maintenance

### PROPER MAINTENANCE:

#### Immediate Care after installation

- Keep traffic to a minimum during the first 24 hours to allow the adhesive to harden. Then open to light foot traffic for the next 24 hours.
- Normal traffic can be allowed after 48 hours.
- Furniture should not be placed on the floor for 24 hours so the adhesive (and grout, if applicable), have adequate time to dry.
- Always move heavy furniture and appliances with care to avoid gouging or tearing the floor.
- For swiveled-type office chairs and other rolling furniture with broad surface use non-staining rubber casters at least 2" in diameter.
- Remove small diameter buttons from the legs of straight chairs or other heavy furniture and replace with metal glides that have bearing surfaces not less than 1" in diameter.
- Do not wet-wash, scrub or strip the floor for a minimum of 7 days following installation.
- Resilient flooring, like other types of smooth floors, can become slippery when wet. Allow time for the floor to dry after washing.
- Keep the room temperature between 65° ~ 85°F for at least 48 hours after installation.

#### Regular Care

- Maintain the room temperature between 55° ~ 85°F.
- Always protect floors when moving heavy objects to prevent permanent scratches and tears.
- Use appropriate wide floor protectors under tables, chairs, and any heavy furnishing to avoid permanent damage.
- Place walk-off mats at all entrances, it helps protect the floor from water, grease, sand and dust floor cleaner.
- Avoid one-step "mop and polish" products, dishwashing liquids and oil-based cleaners. These may leave a residue which can attract dirt and dull your floor's finish. Avoid cleaners that contain abrasives or solvents which may permanently damage the floor.
- Remove excess water after washing the floor.
- Use of blinds or curtains is recommended during peak sunlight hours. Direct sunlight can result in discoloration and volatile temperature variations causing damage to the floor.
- Do not allow solvent into the seams, this may cause it damage or become moldy.
- Use a dry cloth or vacuum cleaner without a beater bar for cleaning. When water or any cleaning liquid is used, please squeeze out all water for cleaning.
- All stain-forming and aggressive substances must be immediately removed from the surface.
- Maintain with quality vinyl floor cleaning products recommended by your Floorcovering supplier for the type of area that is being installed.