

DAVENPORT HD PORCELAIN TILE

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE				LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	ICE	ASH	EARTH	MICA					
16" x 32" DAVENPORT HD PORCELAIN TILE	65-522	65-523	65-524	65-525	60.48	4	13.78	22	303.16
12" x 24" DAVENPORT HD PORCELAIN TILE	69-399	69-400	69-401	69-402	60.40	8	15.50	32	496.00
13" x 13" DAVENPORT HD PORCELAIN TILE	63-640	63-641	63-642	63-643	45.10	11	12.91	58	748.90
3" x 12" DAVENPORT HD PORCELAIN BULLNOSE	63-580	63-581	63-582	63-583	16.46	20	n/a	84	1680 pcs.
2" x 2" DAVENPORT HD PORCELAIN BASKETWEAVE	63-576	63-577	63-578	63-579	38.45	10	9.69	48	465.12

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	16" x 32"	12" x 24"	13" x 13"
THICKNESS		mm - in	9.8 mm - 3/8"	9mm - 11/32"	7.7 mm - 5/16"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4	4	4
SCRATCH HARDNESS		(Mohs)	8	8	8
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 350	≥ 350	≥ 350
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class B - Res.	Class B - Res.	Class B - Res.
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60	≥ 0.60	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.80	≥ 0.80	≥ 0.80
DCOF (WET)	ANSI B101.3		≥ 0.50	≥ 0.50	≥ 0.50
SHADE VARIATION			V3	V3	V3



12" x 24" DAVENPORT ASH HD PORCELAIN TILE