ScubaSeal Tile Floor Care

To keep the lasting shine and fresh feel of your investment for as long as possible, we recommend that you:

Do

- Wipe up spills as soon as possible. Never use highly abrasive scrubbing tools on any resilient floor.
- Wash your floor occasionally with an approved Floor Cleaner.
- Use only an approved polish to return your floor's original shine if it begins to dull over time.

Don't

- Use detergents, abrasive cleaners or "mop and shine" products – they may leave a dull film on your floor.
- Use paste wax or solvent-based polishes.
- Use rolling casters as they can damage the floor.
- Use a beater bar when vacuuming because it can visibly damage the floor surface.
- Use highly abrasive scrubbing tools.

Proactive protection for your floor

- When moving appliances or heavy furniture, lay a plywood panel on your floor and "walk" the item across it. This protects your floor from scuffing and tears.
- Use floor protectors on furniture to reduce indentation. As a general rule of thumb, the heavier the item, the wider the floor protector needed.
- Be careful with rolling casters. They can damage the floor. Therefore, we do not recommend them. If you choose to use them, the double wheel type are the best option.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home. We do not recommend the use of rubber- or latex-backed mats (except where noted) because the chemical (antioxidant) used to keep the backing from becoming brittle can permanently stain your floor. We suggest a non-staining vinyl-backed mat or a woven rug that is colorfast. Most of these products are identified "colorfast" by the manufacturer.

Immediately after installation

- Maintain a minimum room temperature between 65 and 85 degrees Fahrenheit for 48 hours after installation is completed.
- We recommend that you do not scrub or wash your floor for five days.

  - To view video, press arrow

  - After viewing to continue reading install instructions, press Esc