



OAK BISBEE

Oak Bisbee is a 3-strip floor with moderate color variations and a brown stain. May contain minor knots.



						179111.2
PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK5MUW240	Joint	Woodloc® 5G	Moisture	EN13183	7%±2%
EAN Code	7393969034180	Floor heating	Yes	content		
Surface Treatment	Silk matte finish	Warranty	25 years	Minimun Mean Density kg/m³ >500 kg/m³		
Dimensions	95 3/8 x 7 7/8 x 1/2"	Wear Layer Thickness	1/8"	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	54 lbs	(mm)		Formaldehyde	EN717-1	E1
Area per Package	36.6 sqft		1/2"	Emission		
Area per pallet (m²)	0 sqft	Installation method	Floating, Glue-Down	Content PCP	CEN/TR14823	3 ≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.			Breaking Strength N/mm²	EN1533	NPD
DETAIL DESCRIPTION		_		Thermal Conductivity	EN12664	0,14 W/mK
Naturally occuring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.				Thermal Resista	ance R-Value	.09 (m2K/W)
				Biological Durability	EN350-2	Class 1
COLOR CHANGE				CARB2		Compliant
Stained product - noticable color change over time.				Slipperiness	CEN/TS15676	5 NPD

CERTIFICATES







Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.