



## OAK MUSE

Oak Moire have a 1-strip design, matt finish and some knots.



PRODUCT DETAILS FAC		ACTS		TECHNICAL PROPERTIES		
13103AEK1VKW185	Design	1-strip	Moisture	EN13183	7%±2%	
7393969043120	Grading	Variation		ntent		
Matte finish	Range	Kährs Avanti	Minimun Mean Density kg/m³ >500 kg/m³			
73 1/4 x 5 x 1/2"	Collection	Canvas Collection	Reaction To Fire	EN13501-1	Dfl-s1	
28 lbs	Resandable	2 times	Formaldehyde Emission	EN717-1	E1	
17.8 sqft	Natural/Stained	Stained				
1120.3 sqft	Brinell Value	3,7	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Package infoPackages may containstart and stop boards.	Joint	Woodloc®	Breaking Strength N/mm²	EN1533	NPD	
	Floor heating	Yes				
			Thermal	EN12664	0,08 W/mK	
Even colour with minor variations. Small sized knots in limited numbers allowed.		25 years Con	Conductivity			
		Hardwood	Thermal Resistance R-Value		.15 (m2K/W)	
	Wear Layer Thickness (mm)	1/8"	Biological Durability	EN350-2	Class 1	
Stained product - noticable color change over time.		Pine/Spruce lamella	CARB2		Compliant	
		1/2"	Slipperiness	CEN/TS15676	6 NPD	
	Installation method	Floating, Glue-Down				
	ColourCode	2				
	7393969043120  Matte finish  73 1/4 x 5 x 1/2"  28 lbs  17.8 sqft  1120.3 sqft  Packages may contain start and stop boards.	13103AEK1VKW185 Pesign  7393969043120 Grading  Matte finish Range  73 1/4 x 5 x 1/2" Collection  Resandable  17.8 sqft Natural/Stained  Brinell Value  Packages may contain start and stop boards. Floor heating  Warranty Wear-layer material Wear Layer Thickness (mm)  ble color change over time.  Core material	13103AEK1VKW185  Pesign 1-strip  7393969043120  Grading Variation  Matte finish Range Kährs Avanti  Collection Canvas Collection  28 lbs Resandable 2 times  17.8 sqft Natural/Stained Stained  1120.3 sqft Packages may contain start and stop boards.  Ploor heating  Warranty Variations. Small sized knots yed.  Wear-layer material Wear-layer material Wear-layer Thickness (mm)  Core material Pine/Spruce lamella 1/2"  Installation method Floating, Glue-Down	13103AEK1VKW185 Design 1-strip Moisture content 7393969043120 Grading Variation Matte finish Range Kährs Avanti  73 1/4 x 5 x 1/2" Collection Canvas Collection Fire  28 lbs Resandable 2 times  17.8 sqft Natural/Stained Stained Emission  1120.3 sqft Brinell Value 3,7 Content PCP  Packages may contain start and stop boards. Floor heating Yes  Warranty 25 years  Wear-layer material Hardwood Thermal Conductivity  Wear Layer Thickness (mm)  Die color change over time. Core material Pine/Spruce lamella  1/2"  Installation method Floating, Glue-Down  Moisture content Condents  Minimun Mean Reaction To Fire Formaldehyde Emission  Content PCP  Breaking Strength N/mm²  Thermal Conductivity  Thermal Conductivity  Thermal Resistance Biological Durability  CARB2  Slipperiness	13103AEK1VKW185  Design 1-strip Moisture content  Final Minimun Mean Density kg/m³ Minimun Mean Density kg/m³ Minimun Mean Density kg/m³ Reaction To Fire  EN13501-1 Fire  Endission  EN717-1 Endisplayed Endi	

## **CERTIFICATES**







## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.