

## MauiMtn XL

### Specification

9 3/8" W x 60" L

14mm thickness (12mm+2mm pad)

### Installation

Angle/Angle long side and Unidrop short side

### Product Warranties

Limited lifetime residential

Limited lifetime pet-proof

Limited lifetime waterproof

Limited 15 year light commercial

### Packaging

5 pieces per carton

44.35 lbs. per carton

19.60 SF per carton nominal

52 cartons per pallet

14 pallets per 20' container

22 pallets per 40' container

### Testing Results

100% Allergy Free

No PVC, No plastic, no glue

|  |  |
|--|--|
| NALFA 3.2 Thickness Swell (waterproof):        | 1.2% -1.6% Greatly exceeds heavy duty commercial |
| NALFA 3.7 Wear Resistance:                     | >4,000 Commercial AC4                            |
| CARB II Certified:                             | Exceeds CARB II Standard by more than 90%        |
| FloorScore Certified:                          | TVOC range >0.5mg/m <sup>3</sup>                 |
| NALFA Assembled Joint Surface Swell Test:      | No Change – highest rating available             |
| NALFA 3.5 Large Ball Impact Resistance:        | 1400mm, Class 4 Heavy Commercial                 |
| NALFA 3.6 Small Ball (Dart) Impact Resistance: | 500mm, Class 4 Heavy Commercial                  |
| Accostical IIC, STC:                           | 70, 72   |
| Locking Strength ISO 24334 Long/Short Side:    | 1403 (N)   |