

SeaPerfection

Specification

7 11/16" W x 48" L

10mm thickness (8mm+2mm pad)

Installation

Angle/Angle long side and Unidrop short side

Product Warranties

Limited lifetime residential

Limited lifetime pet-proof

Limited lifetime waterproof

Limited 15 year light commercial

Packaging

8 pieces per carton

31.81 lbs. per carton

20.80 SF per carton nominal

60 cartons per pallet

20 pallets per 20' container

27 pallets per 40' container

Testing Results

100% Allergy Free

No PVC, No plastic, no glue

NALFA 3.2 Thickness Swell (waterproof):	1.2% -1.6% Greatly exceeds heavy duty commercial
NALFA 3.7 Wear Resistance:	>4,000 Commercial AC4
CARB II Certified:	Exceeds CARB II Standard by more than 90%
FloorScore Certified:	TVOC range >0.5mg/m ³
NALFA Assembled Joint Surface Swell Test:	No Change – highest rating available
NALFA 3.5 Large Ball Impact Resistance:	1400mm, Class 4 Heavy Commercial
NALFA 3.6 Small Ball (Dart) Impact Resistance:	500mm, Class 4 Heavy Commercial
Accostical IIC, STC:	70, 72
Locking Strength ISO 24334 Long/Short Side:	1403 (N)